

## MP-800 Rotary Door Closer

### Application

Interior or Exterior Doors  
Weight to 35 lbs.

### Handing

Reversible

### Finish

Aluminum Body

### Features

Small rotary closer regulates door closing speed. Formally known as the Ives C930 Rota-Closer, the MPOWR Model 800 is for use on lightweight interior, screen or storm doors.

- For use with doors up to 35 lbs.
- Non-handed, works with both left and right-handed doors
- Aluminum finish
- Approximate dimensions: 2" Dia. x 3"

### Installation Instructions

Tools Required: Drill 1/8" drill bit, adjustable wrench, flat-head screw driver, awl or pencil.

For Doors Hinged on Right, from Interior Side:  
(Illustrations 1 & 2)

1. Position bracket (A) on hinged side of door with door closed. Mark, drill and secure with long screws.
2. Position bracket (B) as shown. Bottom of Bracket (B) should align with top of Bracket (A). Mark, drill and secure.
3. Attached Closer (C) to bracket (A)
4. Attached closer arm (D) to Bracket (B) in center hole.
5. With door closed, push tension adjustment screw (E) upward to release lock position and turn left. Test closing speed. Turn left to increase closing speed.

For Doors Hinged on Left, from Interior Side:  
(Illustrations 3 & 4)

1. Follow instructions 1 and 2 from above but position brackets as shown in illustrations 3.
2. With closer **unattached** push adjustment screw (E) upward and turn to right on half turn, then follow instructions 3 and 4 above. Test closing speed. Turn right to increase closing speed.

